

Index: P06

Corner: C-W1/16

LAND CORNER RECORD

State of Indiana
Hoosier National Forest

Polk F15

Twnshp: 7N

Range: 1E

Section: 20 2nd P.M.


County: MONROE CO.

Polk_F15


EXISTING SURVEYS

Original Government Survey				Original Survey Evidence Found			
Year Surveyed:		By:		Date of Search:		By:	
Original Monument:				Monument Found:			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Subsequent Corner Restoration				Evidence of Subsequent Corner Restoration Found			
Where Filed or Recorded:		Recorders Office		Year 1906		By: CM Bower	
Book: S.Bk.2		Page: 183		Searched:			
Monument Set:		Stone		Monument Found		Set Stone	
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Black Walnut	5"	S60°E	10 Lks	Sandstone	w/ "W"	East	10 Lks
				Sandstone	w/ "W"	West	10 Lks

OTHER EVIDENCE


Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc.	Sketch of Monument
The monument is located 200 Southwest and perpendicular to Roberts Road, 250' south of where said road turns southeasterly, 6' northwest of the top of a meandering creek bank, 80' south of a draw in flat bottom ground.	

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.			
Center West 1/16; A 0.9'x0.65' sandstone was found flush with the ground with a chiseled groove across the top. This corner was established on a 1891 Legal Survey found in Survey Book 2, page 183-184 by Alexander Spencer. This corner was re-established as shown a 1906 survey by C.M. Bower, found in Volume 3, page 19. One of the witness stones called for on the 1906 survey was found eroded out, in a creek about 10 feet East of the corner.			
Corner Diagram	Accessories: Describe new BTs & witness objects established to perpetuate existing evidence.		
	11" Walnut (in fence running north) N30°E 3.0' 15" Walnut (9' North of top of bank) S45°W 27.5' 9" Maple N70°W 46.0'		
	Referenced on BRG survey recorded as InstNo.2005011737. Accepted by the Monroe County Surveyor Review Board on August 6, 2019.		
	Corner Recordation:		Certificate Prepared:
	Filed and Recorded in County records:		Date:
Book:		Page:	
Geodetic Coordinates:	Lat./N.		Long./E.
Section: 20	Edited By:	BTR	Date Created: 10/2004

Index: P-6	Corner: CW1/16	LAND CORNER RECORD				State of Indiana Hoosier National Forest	
Twnshp: 7N	Range: 1E	Section: 20	2nd P.M.	County	Monroe		
EXISTING SURVEYS							
Original Government Survey				Original Survey Evidence Found			
Year Surveyed:				By:			
Original Monument:				Date of Search:			
Species	Diameter	Bearing	Distance	Monument Found:			
				Species	Diameter	Bearing	Distance
Subsequent Corner Restoration				Evidence of Subsequent Corner Restoration Found			
Where Filed or Recorded:	Monroe County Surveyors Office			Year Searched:	12/12/03	By:	B.Stone
Book: ?	Page: 183	Date: 11/27/1871					
Monument Set:	Stone			Monument Found	9"x 9" triangular shaped stone 10" tall with a 1" diameter notch 9" long on one side		
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
B.Walnut	15"	N 87°E	183 ½ Lks.				

OTHER EVIDENCE	Sketch of Monument
Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc. The stone was partially buried in a wide flat bottom 3 feet north of the 4 foot high north creek bank. A 12" Black Walnut with north, south and west wire stands N 27° E 3.0 feet from the stone. An old moundrow runs to the north with remnants of old fencewire in the trees. Old fence remnants are in a treeline to the west. An open field is south of the creek. Vegetation to the west is open but thicker to the northeast. THE AUTHENTICITY OF THIS STONE IS QUESTIONABLE.	

PERPETUATION RECORD			
Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.			
			
			
Corner Diagram		Accessories: Describe new BTs & witness objects established to perpetuate existing evidence.	
		B. Walnut (with wire) Ash (on the north creek bank with a 13" plastic bucket nailed at the base) 12" 13" N 27° E N 81°E 3.0 Ft. 36.1 Ft.	
		Corner Recordation:	Certificate Prepared:
		Filed and Recorded in County records:	Date:
		Book:	Page:
		State Plane Coordinates: N. 1376866.816 E. 3136165.368	
Section: 20	Edited By: Robert J. Stone		Date Created: 12/15/03